

Copyright 2006 by The American Institute of Architects (AIA)  
 Exclusively published and distributed by Architectural Computer Services, Inc. (ARCOM) for the AIA

METAL-FACED COMPOSITE WALL PANELS							
MANUFACTURER/ MODEL	FIRE-RESISTANT CORE MATERIAL	FACING MATERIAL	METAL THICKNESS INCHES (MM)	EXTERIOR FINISH	JOINT TYPE	PANEL COVERAGE INCHES (MM)	PANEL THICKNESS INCH (MM)
<b>ALCAN COMPOSITES USA INC.</b>							
Alucobond	No	Aluminum	0.020 (0.51)	Fluoropolymer, anodized	Rout and return, rainscreen	Up to 62 (1575)	0.118 (3) 0.157 (4) 0.236 (6)
Alucobond Plus	Yes	Aluminum	0.020 (0.51)	Fluoropolymer, anodized	Rout and return, rainscreen	Up to 62 (1575)	0.157 (4)
<b>ALCOA INC.</b>							
Reynobond PE	No	Aluminum	0.020 (0.51)	Fluoropolymer	Rout and return, rainscreen, glazed in	39.37 (1000) 48 (1219) 60 (1524)	0.118 (3)
						42 (1067) 49.2 (1250) 50 (1270) 62 (1575)	0.157 (4) 0.197 (5) 0.236 (6)
Reynobond FR	Yes	Aluminum	0.020 (0.51)	Fluoropolymer	Rout and return, rainscreen, glazed in	42 (1067) 49.2 (1250) 50 (1270) 62 (1575)	0.157 (4)
			0.028 (0.70)	Fluoropolymer	Rout and return, rainscreen, glazed in	<b>Note 1</b>	0.197 (5)
<b>ALPOLIC; DIVISON OF MITSUBISHI CHEMICAL AMERICA, INC.</b>							
ALPOLIC	No	Aluminum	0.020 (0.51)	Fluoropolymer, siliconized polyester, anodized	Rout and return, rainscreen, glazed in	50 (1270) 62 (1575)	0.118 (3) 0.157 (4) 0.236 (6)
ALPOLIC/fr	Yes	Aluminum	0.020 (0.51)	Fluoropolymer, siliconized polyester, anodized	Rout and return, rainscreen, glazed in	50 (1270) 62 (1575)	0.157 (4) 0.236 (6)
ALPOLIC Copper	No	Copper	0.016 (0.41)	Natural or pre-patinated	Rout and return, rainscreen, glazed in	Up to 36.5 (902)	0.157 (4) 0.236 (6)
<b>CENTRIA ARCHITECTURAL SYSTEMS</b>							
FormaBond	Yes	Aluminum	0.032 (0.81)	Fluoropolymer	Double tongue- and-groove shiplap, rainscreen, glazed in	Up to 60 (1524)	0.315 (8)
<b>CITADEL ARCHITECTURAL PRODUCTS, INC.</b>							
Envelope 2000 (RS)	No	Aluminum	0.024 (0.61)	Fluoropolymer	Rainscreen	Up to 60 (1524)	0.157 (4)
Envelope 2000 (RR)	No	Aluminum	0.024 (0.61)	Fluoropolymer	Rout and return, sealant	Up to 60 (1524)	0.157 (4)

METAL-FACED COMPOSITE WALL PANELS							
MANUFACTURER/ MODEL	FIRE-RESISTANT CORE MATERIAL	FACING MATERIAL	METAL THICKNESS INCHES (MM)	EXTERIOR FINISH	JOINT TYPE	PANEL COVERAGE INCHES (MM)	PANEL THICKNESS INCH (MM)
<b>COPPER SALES, INC.</b>							
UNA-FAB Series 1000	No	Aluminum	0.020 (0.51)	Fluoropolymer, anodized	Rout and return, sealant	Up to 60 (1524)	0.118 (3)
		Copper	0.022 (0.55)	Mill	Rout and return, sealant		Up to 34 (864)
UNA-FAB Series 1500	No	Aluminum	0.020 (0.51)	Fluoropolymer, anodized	Framing system	Up to 60 (1524)	0.157 (4) 0.236 (6)
<b>PROTEAN CONSTRUCTION PRODUCTS, INC.</b>							
ACM 100	Yes	Aluminum	0.020 (0.51)	Fluoropolymer	Rout and return, sealant	Up to 60 (1524)	0.118 (3) 0.157 (4) 0.236 (6)
<b>Note:</b>							
1. For availability, consult the manufacturer.							

\* \* \* \* \*