

TABLE 3 - OPERABLE GLASS PANEL PARTITIONS

MANUFACTURER	PRODUCT	PANEL TYPE	ACOUSTICAL PROPERTIES		MAX. WEIGHT LB/SQ. FT. (KG/SQ. M)	MAX. HEIGHT FEET ¹ (M)	MAX. PANEL WIDTH INCHES ¹ (MM)	MIN./MAX. PANEL THICKNESS INCHES (MM)	MIN./MAX. THICKNES S OF GLASS INCHES (MM)	TOP/ BOTTOM RAILS HEIGHT INCHES (MM)	FRAME STYLE/ MATERIAL
			STC (MAX.)	NRC							
Hufcor	G600 ³	I	N/A	N/A	7.4 (36.1)	12'-2" (3.7)	48 (1219)	1-9/16 (40)	1/2 (12)	4.0 / 4.0 (102 / 102)	Frameless ² Tapered Aluminum
	G600A	I	48	N/A	19.5 (95.2)	11'-8" (2.0)	48 (1219)	3-3/4 (95)	5/8 - 2-1/4 (16 - 57)	5.0 / 5.0 ⁴ (127 / 127 ⁴)	Framed Square Aluminum
	600T	I, P, C	N/A	N/A	7.94 (38.3)	12'-0" (3.7)	48 (1219)	1-3/4 - 2-1/4 (44 - 57)	1/4 - 1.0 (6 - 25)	4.0 / 6.0 (102 / 152)	Framed Wood
KWIK-WALL	CLEAR-DIVISIONS Variotec	I	N/A	N/A	7.4 (36.1)	12'-0" (3.7)	60 (1524)	1-1/2 (38)	1/2 (12)	4-1/8 / 4-1/8 (105 / 105)	Frameless ² Aluminum
	CLEAR-DIVISIONS Cornertec		N/A	N/A	7.4 (36.1)	12'-0" (3.7)	60 (1524)	1-1/2 (38)	1/2 (12)	4-1/8 / 4-1/8 (105 / 105)	Frameless ^{2,5} Aluminum
	CLEAR-DIVISIONS Variofold	C	N/A	N/A	7.4 (36.1)	8'-6-3/4" (2.6)	35-3/8 (899)	1-1/2 (38)	1/2 (12)	4-1/8 / 4-1/8 (105 / 105)	Frameless ² Aluminum
	CLEAR-DIVISIONS Centerfold		N/A	N/A	7.4 (36.1)	8'-6-3/4" (2.6)	35-3/8 (899)	1-1/2 (38)	1/2 (12)	4-1/8 / 4-1/8 (105 / 105)	Frameless ² Aluminum
Modernfold	362SR	I	N/A	N/A	7.4 (36.1)	10'-2" (3.1)	48 (1219)	1-7/8 (48)	3/8 - 1/2 (10 - 12)	3-5/8 / 3-5/8 (92 / 92)	Frameless ² Square Aluminum
	362TR		N/A	N/A	7.4 (36.1)	10'-2" (3.1)	48 (1219)	1-7/8 (48)	3/8 - 1/2 (10 - 12)	3-5/8 / 3-5/8 (92 / 92)	Frameless Tapered Aluminum ²
	600SR		N/A	N/A	7.4 (36.1)	10'-2" (3.1)	48 (1219)	1-7/8 (48)	3/8 - 1/2 (10 - 12)	3-5/8 / 6 (92 / 152)	Frameless Square Aluminum ²
	Acousti-Seal Glass	I, P, C	44	N/A	7.4 (36.1)	12'-2" (3.7)	48 (1219)	3 (76)	1/4 - 2-1/4 (6 - 57)	10.5 / 14.5 (51.2 / 70.8)	Framed Steel
Nana Wall Systems	SL45	P, C	N/A	N/A	5.5 (26.9)	9'-6" (2.9)	43 (1092)	1-3/4 (44)	1/4 - 7/8 (6 - 22)	2-1/4 / 2-1/4 (57 / 57)	Framed Aluminum
	SL70 ⁶	C	41	N/A	8.0 (39.1)	12'-2" (3.7)	43 (1092)	2-3/4 (70)	1/4 - 1-1/2 (6 - 38)	2-1/2 / 2-1/2 (64 / 64)	Framed Aluminum
	VSW35	I	N/A	N/A	5.5 (26.9)	8'-6" (2.6)	47 (1194)	1-3/8 (35)	3/16 - 3/4 (5 - 19)	2.0 / 2.0 (50 / 50)	Framed Aluminum
	VSW65	I	N/A	N/A	5.5 (26.9)	9'-0" (2.7)	39 (991)	2-5/8 (67)	1/4 - 15/16 (6 - 24)	3-3/4 / 3-3/4 (95 / 95)	Framed Wood

TABLE 3 - OPERABLE GLASS PANEL PARTITIONS

MANUFACTURER	PRODUCT	PANEL TYPE	ACOUSTICAL PROPERTIES		MAX. WEIGHT LB/SQ. FT. (KG/SQ. M)	MAX. HEIGHT FEET ¹ (M)	MAX. PANEL WIDTH INCHES ¹ (MM)	MIN./MAX. PANEL THICKNESS INCHES (MM)	MIN./MAX. THICKNESSES OF GLASS INCHES (MM)	TOP/ BOTTOM RAILS HEIGHT INCHES (MM)	FRAME STYLE/ MATERIAL
			STC (MAX.)	NRC							
	WD65	P, C	36	N/A	5.5 (26.9)	9'-6" (2.9)	43 (1092)	2-5/8 (67)	1/4 - 15/16 (6 - 24)	3-1/4 / 3-1/4 (80 / 80)	Framed Wood
	WD66	P, C	N/A	N/A	5.5 (26.9)	9'-2" (2.8)	43 (1092)	2-5/8 (67)	1/4 - 15/16 (6 - 24)	3-1/4 / 3-1/4 (80 / 80)	Framed Wood

Legend:

I = Individual Panels; P = Paired Panels; C = Continuously Hinged Panels; N/A = Not Available or Not Applicable

Notes:

1. Maximum height cannot be achieved with maximum width. They are inversely related.
2. Optional vertical edge trim is available.
3. This model is advertised with optional individual motor drives on each panel.
4. The manufacturer can increase the bottom rail up to 13 inches (330 mm).
5. This model has corner supports at the top and bottom in lieu of top and bottom rails.
6. This model uses thermal-break construction to improve the sound performance.